

Technical Data Sheet

PERMAfun Peach Skin

PRODUCT DESCRIPTION

PERMAfun Peach Skin is a premium polymeric vinyl with a soft, peach-skin like structure and a special adhesive which allows excellent adhesion on all kinds of inkjet digital inks, including UV ones. This film can be used indoor as an overlaminating film of the MACal 9800 Pro range to give very soft, pastel colours, or on digital prints to give them a soft touch and appearance. Used with well chosen visuals of the JT5900 series, it allows to create nice velvet like effects. This MACTac film is designed for indoor, high profile applications over flat to slightly curved surfaces and to create unique effects in eg interior design, hotel decoration ... As it is certified Class C according to DIN 51097, Permafun Peach Skin can also be used as slip resistant laminate for floor graphics in areas where people walk bare-foot.

Face : matt, peach skin texture, cadmium-free thick, semi-transparent polymeric vinyl
Adhesive : high tack, permanent, clear solvent adhesive
Liner : 135g/m² clay coated white paper

PHYSICAL PROPERTIES

	<u>Average values</u>	<u>Test method</u>
<u>Adhesive</u>		
Quick Tack on glass (N/25 mm)	18	FTM 9
Peel 180° on glass (N/25 mm)		
- after 20 minutes	12	FTM 1 (ASTM D 903-49)
- after 24 hours	16	FTM 1 (ASTM D 903-49)
Dimensional stability	< 0.6mm	FTM 14
Flammability	Self-extinguishing	Sample mounted on aluminium
<u>Thickness</u>		
Film + adhesive (μ)	600	ISO 534 (ASTM D 645)

HEAT RESISTANCE

Application temperature range : 5°C to + 40°C
End-use temperature range : - 45°C to + 70°C

For temperatures outside those quoted above, please consult MACTac.

SHELF LIFE

2 years when stored at 15 to 25°C and ± 50 % relative humidity or less.

EXPECTED DURABILITY

The expected vertical outdoor durability of the unprocessed product in Central Europe (Zone 1) is up to 5 years. This information is based on successful real life experience and artificial aging according to ISO 4892-2.

Note : Exposure to severe temperatures, ultra-violet light as well as conditions in Southern European countries, tropical, sub-tropical or desert regions will cause more rapid deterioration. This also applies to polluted areas, high

altitude and south facing exposure. No durability warranty is given for horizontal exposure. For more information, please refer to Technical Bulletin 7.5: "Outdoor Durability of combined MACtac print media and laminates".

RECOMMENDATIONS

- Where exposure to chemicals, solvents or high pressure water hoses is envisaged, it is recommended to seal the edges of the prints with varnish or silicone in order to avoid penetrate
- The use of flat bed laminator is not recommended to laminate UV prints as the pressure is not sufficient to avoid silvering.
- Where possible, always test the proposed construction under actual application and end-use conditions because a 100% multi-purpose adhesive for all substrates does not exist.
- Use soap and water to clean stains. A gentle rubbing with standard detergent should get rid of larger stains. Always test washability on a side part of the material.
- Due to its velvet structure, Permafun Peach Skin is sensitive to strong scratches. Small scratches can be removed by gently rubbing the surface. Lamination onto the substrate should be done with a soft squeegee.
- For optimal results, always use rolls of PeachSkin from the same lot number for doing a job.

APPLICATIONS

1) Used as a cut vinyl :

Application of PERMAfun Peach Skin when used as a cut vinyl is made easier if MACtac pre-spacing tape is used, or can be applied as an overlaminating film with a standard laminator (at 40°C or more to avoid silvering). Where exposure to chemical and solvent spills are likely to occur, edge sealing with a varnish is recommended.

2) In combination with coloured vinyls (Macal 9800 Pro- Macal 8900 Pro – Macal 8300 Pro) : because this is a much thicker complex to apply, MACtac offers a limited warranty on flat to slightly curved surfaces. There is no warranty for PERMAfun Peach Skin on motor vehicle wrap, over rivets and corrugations, complex surface or marine graphics.

3) Used as an overlaminate on prints : to create unique Peach Skin aspect for interior design applications ; only on flat to simply curved surfaces.

IMPORTANT NOTICE

All MACtac products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects.

Published information concerning MACtac products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of MACtac products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.